


TAILSTOCK

STRONG TAILSTOCK



Model No. : TS S O / A - 250



Model No.	(A)Center Height in Vertical (mm/inch)	(B)Overall Height in Vertical (mm/inch)	(C)Width of Tail(mm)	(D)Width of Guide Block(mm)	E (mm/inch)	Table Dia. (mm)	Thru-Hole Dia.(mm)	(H) (mm/inch)	(I) (mm/inch)	Hydro. Clamping Force(kgf · m)	Pen. Clamping Force(kgf · m)	N.W. (kg)
TSSA-120	120/4.72	205/8.07	10	14	170/6.69	φ 120	φ 30	98/3.86	135/5.31	12		35
TSSO/TSSA-170	135/5.31	220/8.66	12	14	170/6.69	φ 120	φ 30	98/3.86	150/5.90		24	40
TSSO/TSSA-250	185/7.28	290/11.42	14		210/8.27	φ 170	φ 36	113/4.45	165/6.50	25	50	80
TSSO/TSSA-320	210/8.27	340/13.39	14	18	260/10.24	φ 250	φ 70	124/4.88	180/7.09	47	94	88
TSSO/TSSA-400	250/9.84	420/16.54	18		340/13.39	φ 320	φ 110	148/5.83	205/8.07	71	142	200
TSSO/TSSA-500	310/12.20	520/20.47	18	22	420/16.54	φ 400	φ 130	158/6.22	230/9.06	92	184	235
TSSO/TSSA-630	400/15.75	660/25.98	20		520/20.47	φ 500	φ 160	180/7.09	275/10.83	125	250	350
TSSO/TSSA-800	480/18.90	805/31.69	20	22	650/25.59	φ 630	φ 230	201/7.91	310/12.20	350	700	450
TSSO-1000	650/25.59	1000/39.37	22		800/31.50	φ 800	φ 300	211/8.31	340/13.39	370	740	680

Tailstock & Table Size Application

Table Model	Manual Tailstock	Auto Tailstock(Oil/Air)	Strong Tailstock
DR-120R	TSM-120	TSA-120	TSSA-120
DR-170R,DR-170B	TSM-170	TSA/TSO-170	TSSO/TSSA-170
DR-250R,DR-250B,DC-250	TSM-250	TSA/TSO-250	TSSA/TSSO-250
DR-320R,DC-320	TSM-320	TSA/TSO-320	TSSA/TSSO-320
DR-400R,DC-400	TSM-400	TSA/TSO-400	TSSA/TSSO-400
DR-500R,DC-500	TSM-500	TSA/TSO-500	TSSA/TSSO-500
DR-630R	TSM-630	TSA/TSO-630	TSSA/TSSO-630
DR-800R	TSM-800	TSA/TSO-800	TSSA/TSSO-800
DR-1000R			TSSO-1000

TSSO/TSSA-120~1000

